



# SHIELD

SITE PROTECTION



# PROTECTIVE HARD SURFACE FILM

## USER GUIDE

- For single use only
- Always test the product for 48 hours on an area of floor prior to use.
- Do not leave this product in place for more than 30 days.
- Do not use on glass or marble surfaces.
- Not suitable for use on carpets, rugs, worn carpets or loose fitting carpet tiles.
- Where applicable ensure underfloor heating is switched off and remains off during application of Shield to the floor surface.
- If subjected to extreme conditions or high temperature, direct sunlight, heavy traffic or outdoor exposure, it is recommended you replace the protective film weekly.
- CAUTION! May cause damage to varnished floors where the curing process has not finished. Please give sufficient time for varnish to fully adhere to the surface prior to applying the Shield Hard Surface Protector.
- Do not apply to a damp surface which will prevent any moisture from evaporating and could cause discolouration and may affect the performance of the product.
- Do not store or use above 35°C or below 5°C. The product should be stored/kept at room temperature 24 hours prior to application.
- USE WITHIN 12 MONTHS OF MANUFACTURE DATE (SEE INNER CORE LABEL).



Easy way to protect your hard surfaces

Ideal protection from spillages, debris, heavy foot traffic during building works, refurbishment, decoration, furniture removal and parties.

- Safer than dust sheets
- One man application
- Easy peel



Fire Rated to both,  
BS EN ISO 9239-1:2002  
BS EN ISO 11925-2:2002



One man application



Protects against spills



Easy peel

[www.TIMco.co.uk](http://www.TIMco.co.uk) · [www.TIMco.ie](http://www.TIMco.ie)