

# EASYSeal Deck Magic

---



## Benefits & Uses

EASY Deck Magic uses the latest advances in chemical technology, so delivering two great benefits in one product. It's a high performance penetrating sealer with the added bonus of greatly improving foot traction to provide a safer grip on wet decking and floors. It achieves this without the use of grit or other unsightly coatings so there are no textural changes to the surface when dry.

Deck Magic will also assist in preserving the life of your timber decking. It can also be used to seal and protect virtually any porous bare or uncoated timber such as fences, sheds, pergolas etc.

## Expectations & Limitations of the Product

**Expectations** EASYSeal Deck Magic will impregnate a bare timber surface. It will provide better grip on wet decking whilst also repelling water penetration, so extending the life of the timber and impeding algae growth.

Can be used "Tanalith E" treated (tanalised) timber.

**Limitations** Not suitable for use on coated timber (i.e. varnished or painted). The timber must absorb the product.

Not suitable for natural stone, porcelain or concrete paving.

Must be applied to clean, dry surfaces.

The timber needs to have been wet for about 5 minutes before the "grip" effect takes place.

**Deck Magic greatly improves foot grip but is slip resistant, not anti-slip.**

## Instructions for Use

**Prior to Use** Always test a small area before use to ensure compatibility and that the finished result is acceptable.

**This product is not suitable if surfaces are non-porous e.g. waxed, sealed or varnished**

Surface should be clean, dry and free from mould, algae and efflorescence before applying.

If the timber has been cleaned prior to application all traces of the cleaner must be removed from the surface, as remaining residue could impede the absorption and effectiveness of the product.

Do not use in wet weather or if rain is forecast within 4 hours of application.

Ideal ambient and surface operating temperature is between 10°C to 20°C.

As a guide ensure the surface of the timber is cool to touch.

Do not apply in direct sunlight. In hot weather conditions apply early in the morning before surface temperature starts to rise.

Ensure footwear is clean or wear protectors to avoid contamination.

Keep pets away until surface is fully dry.

Clean tools and other equipment with warm soapy water immediately after use.

## Application

Use neat as supplied.

Shake well before use.

Apply a generous even coat. We recommend using a long pile roller or low pressure sprayer.

Mop up pooling with a rag or lint free cloth as you go but ensure sufficient is applied to soak into the timber.

## Decking and timber floors

On brand new bare decking apply 1 generous coat.

On 2-5 year old decking apply 2 coats. Allow approx. 2 hours between coats.

5+ year old decking apply 2-3 coats depending on porosity

## On all other wood structures

Apply 1 or 2 coats depending on porosity. If liquid disappears from surface quickly, apply a 2nd coat within 2 hours of the first.

Improved performance is achieved by applying subsequent coats 1 - 2 hours after the previous coat is touch dry. Full performance is reached in 3 -7 days depending on the timber.

Spillages or contaminants such as grease, oil, etc. should be removed immediately

Re-treat with EASY Deck Magic as necessary to maintain optimum performance. Lightly used surfaces will last longer. Heavy traffic areas may need retreating more frequently

NOTE: Coverage depends on the porosity of the surface and its texture. If the surface is particularly uneven or particularly porous, more liquid will be used.

## Examples of the issues arising from inappropriate or incorrect application

- Poor non-slip properties
- There are very few things that can go wrong. The most likely is a lower than expected performance. This will either be caused by either:
1. Insufficient product being absorbed into the timber, either caused through improperly cleaned timber or an old coating having not been fully removed, so preventing the product absorbing into the material, or
  2. Insufficient product being applied – most likely when working with older timber that will require more coats than new.

**Note**                    **This product is extremely difficult to remove once applied.**

## Storage & Display

Do not store or display below 5°C. Keep out of direct sunlight and protect from frost.

## Health & Safety

Keep out of reach of children

Do not breathe spray

Do not get in eyes, on skin, or on clothing.

Wear protective gloves/protective clothing/eye protection/ face protection.

IF SWALLOWED: Immediately call a POISON CENTER or doctor.

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Note**                    Harmful to plants and aquatic life. May be harmful to pets and wildlife when wet.